

Amendments to the Claims:

The following Listing of Claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims

Please amend claims 1, 30 and 36, such that the status of the claims is as follows:

1. (Currently Amended) A delivery system for a composition, the system comprising a container, the container comprising:

an outer housing having a first chamber and a top surface;

a first mass of a first component of the composition, the first mass received in the first chamber, ~~wherein the first component is a liquid;~~

an inner housing received in the first chamber at a first position such that an interference fit exists between the outer housing and the inner housing such that the inner housing seals the first mass within the first chamber, the inner housing having a second chamber and a top surface, a bottom wall and a side wall, the inner housing having an aperture in ~~[[a]]the side wall of the second chamber, and the second chamber having a bottom wall and a side wall;~~

a second mass of a second component of the composition, the second mass received in the second chamber, and the second mass conforming to the bottom wall and the side wall; and

a first seal which is bonded to the top surface of the inner housing and which is bonded to the top surface of the outer housing and which seals the second mass within the second chamber and which seals the first mass within the first chamber.

2. (Original) The delivery system of claim 1 wherein the container further comprises a stop member disposed on the outer housing wherein contact between the inner housing and the stop member occurs at the first position.

3. (Original) The delivery system of claim 2 wherein the stop member is an annular rib.

4. (Original) The delivery system of claim 1 wherein the seal is a foil seal.
5. (Original) The delivery system of claim 1 in which the outer housing further comprises an outer skirt surrounding the first chamber.
6. (Original) The delivery system of claim 5 wherein the skirt has a first girth dimension at a top section thereof, the skirt has a second girth dimension at a bottom section thereof, and the skirt has a third girth dimension at a section intermediate the top section and the bottom section, wherein the third girth dimension is less than the first girth dimension and the third girth dimension is less than the second girth dimension.
7. (Original) The delivery system of claim 1 wherein the container further comprises: a depression in an outer wall of the inner housing proximate the aperture; and a second seal positioned within the depression intermediate the aperture and the outer housing.
8. (Original) The delivery system of claim 7 wherein the depression has a first depth at a top section thereof and a second depth at a bottom section thereof, wherein the first depth is less than the second depth.
9. (Original) The delivery system of claim 7 wherein the second seal is an o-ring.
10. (Original) The delivery system of claim 7 wherein the outer housing further comprises a ramp.
11. (Original) The delivery system of claim 1 wherein a wall of the first chamber is flexible.
12. (Original) The delivery system of claim 1 wherein a wall of the second chamber is flexible.

13. (Original) The delivery system of claim 1 wherein the second component is a liquid.
14. (Original) The delivery system of claim 1 wherein the second component is a solid.
15. (Original) The delivery system of claim 1 wherein the inner housing is a cylinder and wherein the aperture is symmetrical about a radius of the cylinder.
16. (Original) The delivery system of claim 1 further comprising an applicator, the applicator comprising:
- an elongated body having a first end and a second end, the body having a first girth dimension;
 - an applicator tip at the first end of the body; and
 - a projection having a widest point positioned intermediate the first end and the second end, the projection having a second girth dimension at the widest point greater than the first girth dimension.
17. (Original) The delivery system of claim 16 wherein each girth dimension is a circumference.
18. (Original) The delivery system of claim 16 wherein the second chamber has a first length dimension and wherein a distance from the first end of the elongated body to the widest point of the projection is less than or equal to the first length dimension.
19. (Original) The delivery system of claim 16 wherein the inner housing has an inner diameter and wherein the second girth dimension is less than the inner diameter.
20. (Original) The delivery system of claim 16 wherein the applicator tip is a brush.

Application No.: 10/798649

Case No.: 59605US002

21. (Original) The delivery system of claim 1 further comprising an applicator, the applicator comprising:

- an elongated body having a first end and a second end;
- a head at the first end of the body, the head having a first end and a second end, the second end of the head being proximate the first end of the body, the head having a larger girth dimension proximate its second end and a smaller girth dimension proximate its first end; and
- a tip at the first end of the head.

22. (Original) The delivery system of claim 21 wherein the applicator further comprises:

- a shoulder disposed at an interface between the body and the head.

23. (Original) The delivery system of claim 22 wherein the applicator further comprises:

- a stop member disposed on the elongated body, a distance from the shoulder to the stop member being approximately equal to a distance between an upper surface of the inner housing and a upper surface of the outer housing when the inner housing is fully inserted into the first chamber of the outer housing.

24. (Original) The delivery system of claim 21 wherein the applicator further comprises:

- a plurality of brush elements disposed on the tip.

25. (Original) The delivery system of claim 21 wherein the body is hollow and the head comprises an air vent disposed thereon.

26. (Canceled)

27. (Original) The delivery system of claim 1 wherein the inner housing includes a plurality of apertures in the side wall of the second chamber, the apertures being equally spaced about a periphery of the side wall.

Application No.: 10/798649

Case No.: 59605US002

28. (Original) The delivery system of claim 1 wherein the delivery system is used in a dental procedure.
29. (Original) The delivery system of claim 1 wherein the composition is hardenable.
30. (Currently Amended) A method of assembling a composition container comprising:
- providing an outer housing having a first chamber and a top surface;
 - at least partially filling the first chamber with a first mass of a first component of the composition, ~~wherein the first component is a liquid~~;
 - inserting an inner housing into the first chamber until the inner housing is at a first position, wherein an interference fit exists between the outer housing and the inner housing such that the inner housing seals the first mass within the first chamber, the inner housing having a second chamber and a top surface, the second chamber having a bottom wall and a side wall, and the inner housing having an aperture in ~~[[a]]the~~ side wall of the second chamber;
 - at least partially filling the second chamber with a second mass of a second component of the composition, ~~the second mass conforming to the bottom wall and the side wall~~; and
 - sealing the second mass within the second chamber and the first mass within the first chamber by bonding a first seal to the top surface of the inner housing and to the top surface of the outer housing.
31. (Original) The method of claim 30 wherein the outer housing further comprises a stop member and wherein the step of inserting the inner housing into the first chamber includes sliding the inner housing into the first chamber until the inner housing contacts the stop member.
32. (Original) The method of claim 30 wherein the inner housing further comprises a depression in an outer wall of the inner housing proximate the aperture, the method further comprising:

Application No.: 10/798649

Case No.: 59605US002

positioning a seal within the depression prior to inserting the inner housing into the first chamber in a first direction.

33. (Original) The method of claim 32 further comprising pulling back on the inner housing in a second direction opposite the first direction to seat the seal intermediate the aperture and the outer housing.

34. (Original) The method of claim 32 wherein the outer housing further comprises a ramp member, wherein the inner housing contacts the ramp member at the first position, and wherein the ramp member causes the inner housing to move in a second direction opposite the first direction to seat the seal intermediate the aperture and the outer housing.

35. (Canceled)

36. (Currently Amended) A method of providing a composition comprising:
providing a container, the container comprising:
an outer housing having a first chamber and a top surface;
a first mass of a first component of the composition, the first mass received in the first chamber, ~~wherein the first component is a liquid;~~
an inner housing received in the first chamber, the inner housing having a second chamber and a top surface, the second chamber having a bottom wall and a side wall, and the inner housing having an aperture in ~~[[a]]~~the side wall of the second chamber;
a second mass of a second component of the composition, the second mass received in the second chamber, ~~the second mass conforming to the bottom wall and the side wall;~~
and
a seal which is bonded to the top surface of the inner housing and which is bonded to the top surface of the outer housing and which seals the second mass within the second chamber and which seals the first mass within the first chamber;
breaking the seal; and

Application No.: 10/798649

Case No.: 59605US002

providing a force on the inner housing, thereby pushing the inner housing into the outer housing, wherein a pressure caused by the force forces the first mass through the aperture and into the second chamber to mix with the second mass to form the composition.

37. (Original) The method of claim 36 wherein the step of providing a force includes pushing downward on an applicator.

38. (Original) The method of claim 36 wherein the step of breaking the seal includes pushing downward on the seal with the applicator.

39. (Original) The method of claim 38 wherein the applicator comprises a projection and wherein the projection pushes broken parts of the seal toward an inner wall of the inner housing.

40. (Original) The method of claim 37 further comprising:
agitating the composition with the applicator to further mix the first mass and the second mass.

41. (Original) The method of claim 36 wherein substantially all of the first mass enters the second chamber.

42. (Original) The method of claim 36 wherein the inner housing seals the first mass within the first chamber.

43. - 45. (Canceled)